



WALL-MOUNTED AND RECESSED TITAN

TITAN C95 / TITAN E



Specifications:

- Luminaire resistant to extreme vandalism
- Wall-mounted version (Titan C95) or recessed (Titan E)
- 1 mm thick zinc-coated steel body protected against corrosion
- 2 mm thick zinc-coated steel frame protected against corrosion
- Polyester powder coating
- Clear textured polycarbonate diffuser (fluorescence)
- Opal polycarbonate diffuser (LED)
- Tamperproof stainless steel screws

● RAL7016

○ RAL9003
White colour on request

Options:
(please contact us)

Class II
Separate circuit
Duroflam® diffuser
Opal polycarbonate diffuser
1W or 3W LED night light
Built-in microwave motion detection
Daylight sensor (preset to 70 lux)

EXISTING INSTALLATIONS:

Switch to LED!
see p. 202 - 203

LED module:

- 6 x 1.5 W LED module
- Mounted on aluminium heat dissipation plate
- Average colour temperature: 3800 K / IRC (Ra) > 80
- LED power supply: constant voltage 24 V DC
- Total module power: 9.50 W
- Average service life 50000 hours at 25 °C ambient temperature

Corridor function:

By default, the Corridor function provides standby lighting by reducing the luminous flux to 10% of its rated value. On request, we can also preset the fittings to operate with a switch-off warning signal, i.e. to reduce then stop the luminous flux.

Light fittings without built-in motion sensor:
The Corridor function can be activated by another master luminaire, a remote detector, a timer switch or a daylight sensor.


Dimmable fluorescence (EEI = A1):

Three types of controls are included in the samedimmable HF ballast:
DALI, DSI, or SWITCH-DIM (momentary push-button switch operated).

HF ballast (EEI = A2):

- Warm cathode HF ballast
- Non dimmable
- Power factor $\cos \phi > 0.95$

TITAN C95



LED

220-240 V AC / 50 Hz RoHS

	Number of 6 x LED modules	Wattage	Length (mm)	Equivalence ^(*)	Code
	2	23 W	720	1 x 18 W	LD1100
	4	46 W	720	2 x 18 W	LD1101
	4	46 W	1 330	1 x 36 W	LD1102
	8	92 W	1 330	2 x 36 W	LD1103
	6	69 W	1 630	1 x 58 W	LD1104
	12	138 W	1 630	2 x 58 W	LD1105

(*) Equivalences given for information only.

FLUORESCENCE


220-240 V AC / 50 Hz RoHS

LAMP		Length (mm)	Conventional ballast	HF ballast	DALI dimming + Corridor function ⁽¹⁾
1 x 18 W T8	G13	720	LD6455	LD6455-BHF	LD6455-BHD
2 x 18 W T8	G13	720	LD6454	LD6454-BHF	LD6454-BHD
1 x 36 W T8	G13	1 330	LD6453	LD6453-BHF	LD6453-BHD
2 x 36 W T8	G13	1 330	LD6452	LD6452-BHF	LD6452-BHD
1 x 58 W T8	G13	1 630	LD6451	LD6451-BHF	LD6451-BHD
2 x 58 W T8	G13	1 630	LD6450	LD6450-BHF	LD6450-BHD
1 x 14 W-24 W T5	G5	720	-	LD6600	LD6600-BHD
2 x 14 W-24 W T5	G5	720	-	LD6602	LD6602-BHD
1 x 28 W-54 W T5	G5	1 330	-	LD6604	LD6604-BHD
2 x 28 W-54 W T5	G5	1 330	-	LD6606	LD6606-BHD
1 x 35 W-49 W T5	G5	1 630	-	LD6608	LD6608-BHD
2 x 35 W-49 W T5	G5	1 630	-	LD6610	LD6610-BHD

(1) Requires external control (remote motion sensor or other master luminaire, etc.) to activate the Corridor function.

Tamperproof tool see pages 204-205.

TITAN E



Recess dimensions:
R x 210 mm x 100 mm

LED

220-240 V AC / 50 Hz RoHS

	Number of 6 x LED modules	Wattage	Length (mm)	Equivalence ^(*)	Code
	2	23 W	730	1 x 18 W	LD1200
	4	46 W	730	2 x 18 W	LD1201
	4	46 W	1 340	1 x 36 W	LD1202
	8	92 W	1 340	2 x 36 W	LD1203
	6	69 W	1 640	1 x 58 W	LD1204
	12	138 W	1 640	2 x 58 W	LD1205

(*) Equivalences given for information only.

FLUORESCENCE

220-240 V AC / 50 Hz RoHS

LAMP		Length (mm)	Conventional ballast	HF ballast	DALI dimming + Corridor function ⁽¹⁾
1 x 18 W T8	G13	730	LD6475	LD6475-BHF	LD6475-BHD
2 x 18 W T8	G13	730	LD6474	LD6474-BHF	LD6474-BHD
1 x 36 W T8	G13	1 340	LD6473	LD6473-BHF	LD6473-BHD
2 x 36 W T8	G13	1 340	LD6472	LD6472-BHF	LD6472-BHD
1 x 58 W T8	G13	1 640	LD6477	LD6477-BHF	LD6477-BHD
2 x 58 W T8	G13	1 640	LD6476	LD6476-BHF	LD6476-BHD
1 x 14 W-24 W T5	G5	730	-	LD6650	LD6650-BHD
2 x 14 W-24 W T5	G5	730	-	LD6652	LD6652-BHD
1 x 28 W-54 W T5	G5	1 340	-	LD6654	LD6654-BHD
2 x 28 W-54 W T5	G5	1 340	-	LD6656	LD6656-BHD
1 x 35 W-49 W T5	G5	1 640	-	LD6658	LD6658-BHD
2 x 35 W-49 W T5	G5	1 640	-	LD6660	LD6660-BHD

(1) Requires external control (remote motion sensor or other master luminaire, etc.) to activate the Corridor function.

Tamperproof tool see pages 204-205.