



LEAF code 2988.AC

Half recessed flangeless luminaire.


LEAF, whenever installed, becomes integral part of the wall/ ceiling and its application creates a "moving" effect on shapes and volumes.


Wall and ceiling mounting. Vertical and horizontal mounting. Installation into plasterboard or brick.

(see the special instructions for brick).

AirCoral® Body.

Supplied c/w wiring.





TECHNICAL FEATURES

Туре Material Absorption capacity* Weight Mounting IP rating Control gear Cut out for plasterboard Lamp type Lamp wattage Luminous efficacy Light distribution Fitting Light Colour Light Colour Voltage connection CRI Emergency Energy efficiency class

Wall and ceiling lamp AC: AirCoral® 10.7 m² 4.5 Kg Wall half recessed IP20 Constant current electronic driver 410 x 410 mm LED 350mA 6W 810 lm - 3000K Wide beam 120° -White 3000K White 2700K - 4000K (on request)

White 2700K - 4000K (on request) 220-240V · 50-60Hz (110V on request) >80

(ह 🔻 🗆 🖉 🖻

(on request) (on request)

FOR FURTHER INFORMATION PLEASE CONSULT THE GENERAL CATALOGUE BUZZI & BUZZI

*The absorption capacity per m3 calculated by the American organization TCNA is parametrized for an average room of 2,7m in height and therefore expressed in m2

A+

Buzzi & Buzzi reserves itself the faculty to change or to modify, without advance notice, the dimensions and the technical characteristics of the products indicated in this catalogue, due to operative necessities to improve the functionality or updating with law regulations.