




## LENTIL

code 6358.AC

Recessed flangeless luminaire.  
Wall and ceiling mounting.  
Installation into plasterboard or brick.  
(see the special instructions for brick).  
Body in AirCoral®.



## TECHNICAL FEATURES

Type	Downlight 45° - Wall lamp 45°
Material	AC: AirCoral®
Absorption capacity*	2.29 m <sup>2</sup>
Weight	1 Kg
Mounting	Wall and ceiling recessed
IP rating	IP40
Control gear	Constant current electronic driver
Cut out for plasterboard	120 x 155 mm
Lamp type	LED
Lamp wattage	1W - 350 mA   2W - 500 mA
Luminous efficacy	75 lm/W - 3000K
Light distribution	Wide beam 120°
Fitting	-
Light Colour	White 3000K
Light Colour	White 2700K (on request)
Light Hole	50 x 100 mm
Voltage connection	220-240V · 50-60Hz
CRI	>80
Emergency	-
Energy efficiency class	A++

## OPTIONAL

H8350	Constant current electronic driver suitable for n°1 code 6358.AC - 350 mA
H8500.B	Constant current electronic driver. Remote installation suitable for n°5 code 6358.AC - 500 mA
H8500.C	Constant current electronic driver. Remote installation suitable for n°2 code 6358.AC - 500 mA
H8500.D	Constant current electronic driver suitable for n°1 code 6358.AC - 500 mA
Available dimmable	PUSH or DALI, remote installation

\*The absorption capacity per m<sup>3</sup> calculated by the American organization TCNA is parametrized for an average room of 2,7m in height and therefore expressed in m<sup>2</sup>



FOR FURTHER INFORMATION PLEASE CONSULT THE GENERAL CATALOGUE BUZZI & BUZZI

Buzzi & Buzzi reserves itself the faculty to change or to modify, without advance notice, the dimensions and the technical characteristics of the products indicated in this catalogue, due to operative necessities to improve the functionality or updating with law regulations.