






### Nightspot B/RGBW Gobo pole luminaire

**Monochrome:** With 1 x high performance LED module, CRI: > 70, Colour tolerance: max. 4 SDCM  
Service life: L70/B20 > 50 000 h  
protection class I or II, IP67 , IK08  
integral driver (AC/DC)



**RGBW:** With 1 x RGBW high performance LED module, protection class I, IP67 , IK08  
external DMX-controller required, connection with hybrid cable 230 V/DMX, RDM compatible integral driver (AC/DC)

windage area AW 0.085 m<sup>2</sup>,  
corrosion-resistant die cast aluminium housing AlSi12 and aluminium profile, polyester powder coated, focusable lens, carrier for gobos and colour filters, all exterior steel parts are stainless steel, tempered safety glass, silicon gasket, closure with 4 stainless steel screws, for pole diameter Ø 60–100 mm, rotatable, powder coated aluminium mounting base: 2 drilled holes Ø 9 mm, spacing 105 mm, 1 centre hole Ø 22 mm, tilt range 80°, swivel range 180°, M20 cable gland





#### Nightspot B Gobo pole luminaire, 63 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
<b>8 987 244 059</b>	black	1 x LED module 47 W	1000 lm	30°
<b>8 987 264 059</b>	white	cool white (6500 K)		
<b>8 987 254 059</b>	silver grey			



#### Nightspot B Gobo pole luminaire, 85 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
<b>8 987 244 049</b>	black	1 x LED module 47 W	1095 lm	20°
<b>8 987 264 049</b>	white	cool white (6500 K)		
<b>8 987 254 049</b>	silver grey			





#### Nightspot B Gobo pole luminaire, 150 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
<b>8 987 244 019</b>	black	1 x LED module 47 W	907 lm	12°
<b>8 987 264 019</b>	white	cool white (6500 K)		
<b>8 987 254 019</b>	silver grey			



Part number*	Protection class I luminaire
<b>1..</b>	<b>Dimmable version (DALI)</b>
<b>2..</b>	<b>Dimmable version (1-10 V)</b>
	Protection class II luminaire
<b>5..</b>	<b>Luminaire not dimmable</b>
<b>6..</b>	<b>Dimmable version (DALI)</b>
<b>7..</b>	<b>Dimmable version (1-10 V)</b>

\*Luminaires available in 2700 K or 3000 K on request





#### Nightspot B RGBW Gobo pole luminaire, 63 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
<b>8 987 249 059</b>	black	1 x LED module RGBW	max.	30°
<b>8 987 269 059</b>	white	W = 6000 K	525 lm	
<b>8 987 259 059</b>	silver grey	(max. 38 W)		



#### Nightspot B RGBW Gobo pole luminaire, 85 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
<b>8 987 249 049</b>	black	1 x LED module RGBW	max.	20°
<b>8 987 269 049</b>	white	W = 6000 K	575 lm	
<b>8 987 259 049</b>	silver grey	(max. 38 W)		



#### Nightspot B RGBW Gobo pole luminaire, 150 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
<b>8 987 249 019</b>	black	1 x LED module RGBW	max.	12°
<b>8 987 269 019</b>	white	W = 6000 K	476 lm	
<b>8 987 259 019</b>	silver grey	(max. 38 W)		

LED (see page 185)

