

**18|19**

ARCHITECTURAL  
OUTDOOR & INDOOR  
LED LIGHTING

**NOVELTIES**

**GRUPO MCI**

# NOVELTIES 18|19

## SMARTLED FLEX® Topflex



- Light to highlight architecture
- Homogenous light without visible dots
- Beam angle 120°
- Up to 865 lm/m
- Flexible linear body
- Round or square shape
- Up to 10 meters per line

NEW

## SQUARE® S & M



- Architectural accent lighting
- Luminous flux range from 500 lm to 2000 lm
- Variety of types: Monocolor, RGBW & SW
- Anti-glare recessed optics
- 7 beam angles: 9°, 20°, 40°, 48x10°, 10x48°, 55° and 75°
- Flush cable gland
- Swivel (360°) and adjustable (180°) projector
- Integrated driver
- Easy serial connection
- Thermal management certificate

NEW

## LINE GRAZER® PLUS



- Powerful wall washer up to 30m
- Lumens output up to 9500lm
- Antiglare luminaire
- Flush wall washer
- 3 beam angles: 12°, 33° and 39x14°
- Perfect color mixing
- Easy serial connection

NEW

## BOW®



- To highlight the outer edge of windows and arches
- Inner louvres to adjust the beam angle on site.
- Beam angle: 180° x 15°
- Leveling luminaire to correct windowsill slope
- 2m wire with lateral or backside cable output

NEW

## LED FLOODSTRIP® PLUS



- 24V and 230V (monocolor 110°) types
- 5 beam angles: 15°, 34°, 47°, 42x25° and 110°
- 4 Light colors: 2700K, 3000K, 4000K and 6000K
- Monocolor, RGB and RGBW types
- Not adjustable and adjustable versions
- Anodized aluminium body and PMMA diffuser

NEW

## SMART DOT®



- Customizable pixel for media applications
- Plug&Play at its finest
- Surface luminaires suitable for indoor and in outdoor use
- Daisy chain up to 32 Dots
- Tall or flat diffuser types
- Different daytime appearances due to several diffuser's finishes
- High output (HO) and low output (LO) versions
- DMX-RDM control (Remote device management)
- Up to 500 lumens output in Ø60x30mm
- Versatility for the cable's input-output

NEW

## HANDRAIL DOT®



- Dot designed to be integrated in new or retrofitted handrails
- Suitable for outdoor: IP66, IK10, and anti-vandalism
- Flat and curved types
- 3 beam angles: 60°, 120° and 90° (asymmetric)
- Luminous efficiency: 100 lm/W
- 316 stainless steel unibody dot
- Polycarbonate lens
- Accessories: Installation tool and M16 Drill jig equipment

NEW

## LINEAR FLEX®



- Cove lighting and other applications
- 3 MacAdam: chromatic stability control
- 4 color temperature: 2700K, 3000K, 4000K and 6000K
- CRI>90, RGB, RGBW, DW and side view types
- Wide range of powers, from 4,8W/m to 33,6W/m
- Dimmable flexible strip
- Up to 3074 lm/m
- It can be cut on size at site
- IP20 and IP67
- Accessories: aluminum profile, diffuser and lenses

NEW LED  
UPDATED

## SMOOTH® 85



- Track and semi-recessed types
- 230V and 110V versions
- Control Type: On-off, DALI and 1-10V
- 3 beam angles: 16°, 24 and 38°
- Lumens output: from 1900lm to 3300lm
- Spotlight efficiency: 105 lm/W
- Integrated multi-power driver inside track adapter
- Spotlight with glass included for easy maintenance
- Passive heat sink
- Smooth design without screws and slots
- Accessories: honeycomb, refractor and soft lens

NEW

## HIGH LITE® Gen2



- Light for high ceilings
- Luminaire efficiency 125 lm/W
- 2 beam angles: 70° and 110°
- Luminous flux range from 5000 to 23000 lm
- Easy changeable driver
- Excellent uniformity
- Extra flat (55 mm) and antiglare
- Modular light fixture every 375 mm
- Thermal test certificate

NEW LED  
UPDATED

## LFS® DOTFREE RGB/W



- Homogenous light without visible dots
- Types Monocolor, **RGB** and **RGBW**
- Adjustable and not adjustable types
- Powers up to 24 W/m
- Small dimensions
- Easy installation and dimmable
- Easy serial connection, up to 10 m

WIDER  
RANGE  
RGB/W

## DOWNITO® 70 IP65



- LED downlight for accent lighting
- IP20, IP40 and **IP65** types
- Smart reflector: active + passive (paintable)
- Luminous flux 1000 lm
- Luminaire efficiency 89 lm/W
- 3 beam angles: 35°, 50° and 70°
- Accessories available: honeycomb, milky diffuser, color filter, etc.
- Thermal test certificate

WIDER  
RANGE  
IP65

#### HEADQUARTERS

##### GRUPO MCI - MUNDOCOLOR HOLDING, S.L.

C/ DELS OFICIS, N° 25  
08850 · GAVÀ  
BARCELONA · SPAIN  
T. (+34) 93 630 28 00  
F. (+34) 93 630 29 66  
M. EXPORT@GRUPO-MCI.COM

#### SUBSIDIARIES

##### MCI MIDDLE EAST FZE

TECHNOHUB 2, 2ND FLOOR,  
OFFICE 232  
DUBAI SILICON OASIS,  
DUBAI (U.A.E)  
P.O.: 342053  
T. +971 56 826 5544  
M. DUBAI@GRUPO-MCI.COM

##### MCI SOUTH EAST ASIA

T. (+65) 9670 1975  
M. SINGAPORE@GRUPO-MCI.COM

[grupo-mci.com](http://grupo-mci.com)