



GARDIAN

Very low consumption
light fitting specially designed
for cellars
and technical rooms

GARDIAN



Specifications:

- Low consumption and weather resistant bulkhead
- Die-cast aluminium with anticorrosion treatment
- Grey polyester powder coating
- Opal prismatic polycarbonate diffuser
- Tamperproof stainless steel screws

● Metallic grey

LED module:




- 8 x 1.2W power LED
- Mounted on aluminium heat dissipation plate
- Average colour temperature: 3800 K / IRC (Ra) > 80
- LED power supply: constant current 350 mA
- Average service life 50000 hours at 25 °C ambient temperature

Compact-Sensor motion detector:



- 5.8 GHz 360° microwave sensor
- Adjustment (potentiometers):
 - Sensitivity 3 to 10 m
 - Daylight sensor 2 to 2000 lux
 - Timer 8 seconds to 20 minutes
- Maximum load: 200 W (fluorescent and LED), 400 W (incandescent)
- Standby power: 0.9 W ± 10%

LED: choice of wattage
Equivalences given for information only



LED

220-240 V AC / 50-60 Hz RoHS

	LAMP	Wattage	Code
	8 LED x 1,2 W	11 W	LL6101
	8 LED x 1,2 W + Compact-Sensor	12 W	LL6102

HALOGEN / FLUORESCENCE

220-240 V AC / 50-60 Hz RoHS

	LAMP		Code
	Max. 1 x 42 W halo. 15 W CFL	E27	LL6103

Tamperproof tool see pages 204-205.