



WALL-MOUNTED AND RECESSED VAUBAN

VAUBAN



Specifications:

- Slim and architectural light fitting
- Wall-mounted (A) or recessed (E) version
- 1 mm thick zinc-coated steel body protected against corrosion
- 2 mm thick zinc-coated steel frame protected against corrosion
- Polyester powder coating
- Clear textured polycarbonate diffuser (fluorescence)
- Opal polycarbonate diffuser (LED)
- Tamperproof stainless steel screws

- RAL7016
- RAL9003
White colour on request

Options:
(please contact us)

Class II
Opal diffuser
1W or 3W LED night light
Separate circuit
Built-in microwave motion detection
Daylight sensor (preset to 70 lux)

EXISTING INSTALLATIONS:

Switch to LED!
see p. 202 - 203

LED module:

- 6 x 1.5 W LED module
- Mounted on aluminium heat dissipation plate
- Average colour temperature: 3800 K / IRC (Ra) > 80
- LED power supply: constant voltage 24 V DC
- Total module power: 9.50 W
- Average service life 50000 hours at 25 °C ambient temperature

Dimmable fluorescence (EEI = A1):

Three types of controls are included in the same dimmable HF ballast:
DALI, DSI, or SWITCH-DIM (momentary push-button switch operated).
Corridor function included: see pages 21-22.

HF ballast (EEI = A2):


- Warm cathode HF ballast
- Non dimmable
- Power factor $\cos \phi > 0.95$

LED version: opal diffuser



VAUBAN A

WALL-MOUNT



LED

220-240 V AC / 50 Hz RoHS

LAMP	Wattage	Equivalence ^(*)	Code
2 x 6 LED 1,5 W	23 W	26 W	LD1800

(*) Equivalences given for information only.

FLUORESCENCE

220-240 V AC / 50 Hz RoHS

LAMP	Conventional ballast	HF ballast	DALI dimming + Corridor function ^(*)
1 x 24 W TC-F	2G10	LD6251	LD6251-BHF LD6251-BHD
1 x 36 W TC-F	2G10	LD6252	LD6252-BHF LD6252-BHD
1 x 11 W TC-S	G23	LD6280	- -
1 x 11 W TC-SE	2G7	-	LD6280-BHF LD6280-BHD
2 x 11 W TC-S	G23	LD6281	- -
2 x 11 W TC-SE	2G7	-	LD6281-BHF LD6281-BHD
1 x 18 W TC-L	2G11	LD6282	LD6282-BHF LD6282-BHD


(*) Requires external control (remote motion sensor or other master luminaire, etc.) to activate the Corridor function.

Tamperproof tool see pages 204-205.



VAUBAN E

RECESSED



Recess dimensions:
L: 400 mm
l: 210 mm
P: 75 mm

LED

220-240 V AC / 50 Hz RoHS

LAMP	Wattage	Equivalence(*) 	Code
2 x 6 LED 1,5 W	23 W	26 W	LD1900

(*) Equivalences given for information only.

FLUORESCENCE

220-240 V AC / 50 Hz RoHS

LAMP	Conventional ballast	HF ballast	DALI dimming + Corridor function(*)
1 x 24 W TC-F	2G10	LD6256	LD6256-BHD
1 x 36 W TC-F	2G10	LD6257	LD6257-BHD
1 x 11 W TC-S	G23	LD6285	-
1 x 11 W TC-SE	2G7	-	LD6285-BHD
2 x 11 W TC-S	G23	LD6286	-
2 x 11 W TC-SE	2G7	-	LD6286-BHD
1 x 18 W TC-L	2G11	LD6287	LD6287-BHD

(*) Requires external control (remote motion sensor or other master luminaire, etc.) to activate the Corridor function.

Tamperproof tool see pages 204-205.

