



RODEO

## RODEO



### Specifications:

- Compact vandal-resistant luminaire
- 1mm thick, zinc-coated steel with anticorrosion protection
- Polyester powder coating
- Braced opal polycarbonate diffuser
- Tamperproof stainless steel screws
- HF ballast  $EEL = A2 \cos \phi > 0.95$

● RAL7016  
Graphite grey

○ RAL9003  
White

Options:  
(please contact us)

Built-in microwave detection  
Daylight sensor (preset to 70 lux)  
Cross-head screws



### LED module:

- 6 x 1.5 W LED module
- Mounted on aluminium heat dissipation plate
- Average colour temperature: 3800 K / IRC (Ra) > 80
- LED power supply: constant voltage 24 V DC
- Total module power: 9.50 W
- Average service life 50000 hours at 25 °C ambient temperature



### Easy-Sensor® detection:


- 5.8 GHz microwave detector
- 360° detection range
- Sensitivity adjustable from 20 to 100%
- Daylight sensor: adjustable from 5 to 2000 Lux
- Adjustable timer: 10 seconds to 20 minutes
- Memorisation of settings in case of power failure
- Maximum load: 500 W (fluorescent and LED), 800 W (incandescent)
- Standby power: 0.9 W  $\pm$  10%
- Operating temperature range: - 20 °C to + 70 °C



### HF ballast (EEL = A2):

- Warm cathode HF ballast
- Non dimmable
- Power factor  $\cos \phi > 0.95$

# RODEO



## LED

220-240 V AC / 50-60 Hz RoHS

	LAMP	Wattage		
	2 x 6 LED 1,5 W	23 W	EP3142	EP3142-C03
	2 x 6 LED 1,5 W + Easy-Sensor® motion detection	24 W	EP3142-DPP	EP3142-C03-DPP

## HF FLUORESCENCE

220-240 V AC / 50-60 Hz RoHS

	LAMP	Wattage		
	1 x 18 W TC-L	2G11	EP3119-BHF	EP3119-BHF-C03
	1 x 24 W TC-F	2G10	EP3125-BHF	EP3125-BHF-C03
	1 x 36 W TC-F	2G10	EP3137-BHF	EP3137-BHF-C03

Tamperproof tool see pages 204-205.

Used for building entrances.

