


### Nightspot A2 LED, pole luminaire

With a high performance LED module and integral temperature monitoring device protection class I, IP65 , IK08 windage area AW 0.035 m<sup>2</sup> die cast aluminium housing, polyester powder coated, rotationally symmetrical aluminium reflector, integral secondary reflector to reduce glare, all exterior steel parts are stainless steel, tempered safety glass, silicon gasket, closure with 4 stainless steel screws, for installation on poles Ø 60 - 100 mm, powder coated aluminium mounting base: 2 drilled holes Ø 9 mm, spacing 105 mm, 1 centre hole Ø 22 mm, tilt range 100°, swivel range 180°, M20 cable gland, integral driver (AC/DC)

#### Nightspot A2 LED, pole luminaire, narrow beam


Part number *	Colour	Light source	Weight	Half beam angle γ
<b>8 983 246 019</b>	black	1 x LED module 33 W	2.5 kg	13°
<b>8 983 266 019</b>	white	warm white (3000 K)		
<b>8 983 256 019</b>	silver grey			

\*These luminaires are also available with neutral white LED (4000 K) upon request.



#### Nightspot A2 LED, pole luminaire, narrow beam


Part number	Description	Half beam angle γ	
		C 0 - 180	C 90 - 270
<b>. . . . . 7.</b>	<b>Luminaire with ribbed glass spreader lens,</b> internally fitted, for linear beam distribution, continuously adjustable through 360°	17°	31°



#### Nightspot A2 LED, pole luminaire, medium wide beam

Part number *	Colour	Light source	Weight	Half beam angle γ
<b>8 983 246 049</b>	black	1 x LED module 33 W	2.5 kg	20°
<b>8 983 266 049</b>	white	warm white (3000 K)		
<b>8 983 256 049</b>	silver grey			


\*These luminaires are also available with neutral white LED (4000 K) upon request.



#### Nightspot A2 LED, pole luminaire, wide beam (without secondary reflector)

Part number *	Colour	Light source	Weight	Half beam angle γ
<b>8 983 246 059</b>	black	1 x LED module 33 W	2.5 kg	67°
<b>8 983 266 059</b>	white	warm white (3000 K)		
<b>8 983 256 059</b>	silver grey			

\*These luminaires are also available with neutral white LED (4000 K) upon request.




Part number	Description
<b>. . . . . 1..</b>	<b>Dimmable luminaire (DALI)</b>
<b>. . . . . 2..</b>	<b>Dimmable luminaire (1-10 V)</b>

#### LED


LEDs, replacement modules available






**Accessories Nightspot A2 LED**

Part number	Colour	Description
<b>129 0 578 940</b>	black	<b>Cowl,</b>
<b>129 0 578 960</b>	white	stainless steel,
<b>129 0 578 950</b>	silver grey	to avoid lateral glare




Part number	Colour	Description
<b>129 0 591 940</b>	black	<b>Protection grill,</b> stainless steel,
<b>129 0 591 960</b>	white	to protect the glass lens from breakage and
<b>129 0 591 950</b>	silver grey	vandalism, for retrofitting



Part number	Colour	Description
<b>129 0 581 000</b>	yellow	<b>Colour filter,</b>
<b>129 0 587 000</b>	red	internally fitted
<b>129 0 583 000</b>	blue	
<b>129 0 588 000</b>	green	




Accessories Nightspot A2 LED, narrow beam		Half beam angle $\gamma$	
Part number	Description	C 0-180	C 90-270
<b>129 0 580 000</b>	<b>Ribbed glass,</b> internally fitted, for linear beam control, continuously adjustable 360°	17°	31°




**Accessories Nightspot A2 LED, with mounting bracket**


Part number	Colour	Description
<b>129 0 390 940</b>	black	<b>Stainless steel earth spike,</b>
<b>129 0 390 960</b>	white	for use in landscape lighting
<b>129 0 390 950</b>	silver grey	




Part number	Colour	Description
<b>128 0 626 940</b>	black	<b>Pole Top Fitter,</b> aluminium,
<b>128 0 626 960</b>	white	for 76 mm pole top, with M20 x 1.5 connection thread,
<b>128 0 626 950</b>	silver grey	for installation of one luminaire




Part number	Colour	Description
<b>119 0 033 940</b>	black	<b>Single pole mount clamp,</b>
<b>119 0 033 960</b>	white	aluminium,
<b>119 0 033 950</b>	silver grey	for poles $\varnothing$ 76 – 89 mm



Part number	Colour	Description
<b>119 0 034 940</b>	black	<b>Double pole mount clamp,</b>
<b>119 0 034 960</b>	white	aluminium,
<b>119 0 034 950</b>	silver grey	for poles $\varnothing$ 76 – 89 mm



Part number	Colour	Description
<b>119 0 031 940</b>	black	<b>Single pole mount arm,</b>
<b>119 0 031 960</b>	white	aluminium,
<b>119 0 031 950</b>	silver grey	for poles $\varnothing$ 76 – 89 mm



Part number	Colour	Description
<b>119 0 032 940</b>	black	<b>Double pole mount arm,</b>
<b>119 0 032 960</b>	white	aluminium,
<b>119 0 032 950</b>	silver grey	for poles $\varnothing$ 76 – 89 mm