



BANG SQUARE


BANG SQUARE



VK35 VK36

Features:

- Vandal-resistant architectural luminaire
- Reinforced polyamide base
- Clear frosted polycarbonate diffuser
- Tamperproof stainless fastenings
- Decorative polycarbonate washers



Option available (please enquire):

- ⊕ Standard screws: add -VST to the product code.




Easy-Sensor® Pro
and Compact Sensor specifications
see pages 16-17





Dimming specifications
Corridor and Extinction warning functions
see pages 18-21

















EB: electronic ballast
Not dimmable EEI = A2
Dimmable EEI = A1 / $\lambda \geq 0.95$



BANG SQUARE



220-240 V AC / 50-60 Hz   RoHS










LAMP					OPAL
 Max. 60 W halo. 23 W CFLi	E27	LB3301	LB3201	LB3101	LB4301
 Max. 2 x 15 W CFLi	E27	LB3311	LB3211	LB3111	LB4311
 1 x 18 W CFLi + Osram Dulux Facility 4000 K	E27	LB3302	LB3202	LB3102	LB4302
 9 W + 9 W TC-SE E.B. dual-powered	2G7	LB3303	LB3203	LB3103	LB4303
 2 x 9 W TC-SE E.B. (2)	2G7	LB3304	LB3204	LB3104	LB4304
 13 W + 13 W TC-DE E.B. (2) dual-powered	G24q-1	LB3305	LB3205	LB3105	LB4305
 1 x 18 W TC-DE E.B.	G24q-2	LB3306	LB3206	LB3106	LB4306
 1 x 18 W TC-DE E.B. (1)	G24q-2	LB3307	LB3207	LB3107	LB4307
 1 x 26 W TC-DE E.B.	G24q-3	LB3308	LB3208	LB3108	LB4308
 1 x 26 W TC-DE E.B. (1)	G24q-3	LB3309	LB3209	LB3109	LB4309
 1 x 32 W TC-TE E.B. (1)	GX24q-3	LB3315	LB3215	LB3115	LB4315

(1) EEI = A2 / $\lambda \geq 0,95$

(2) EEI = A3

BANG SQUARE + STANDBY LIGHT



220-240 V AC / 50-60 Hz   RoHS







LAMP					OPAL
 Max. 60 W halo. 23 W CFLi + LED 1 W	E27	LB3301-CLV	LB3201-CLV	LB3101-CLV	LB4301-CLV
 1 x 18 W CFLi + Osram Dulux Facility 4000 K + LED 1 W	E27	LB3302-CLV	LB3202-CLV	LB3102-CLV	LB4302-CLV
 1 x 18 W TC-DE E.B. + LED 1 W	G24q-2	LB3306-CLV	LB3206-CLV	LB3106-CLV	LB4306-CLV
 1 x 18 W TC-DE E.B. (1) + LED 1 W	G24q-2	LB3307-CLV	LB3207-CLV	LB3107-CLV	LB4307-CLV
 1 x 26 W TC-DE E.B. (1) + LED 1 W	G24q-3	LB3309-CLV	LB3209-CLV	LB3109-CLV	LB4309-CLV
 1 x 32 W TC-TE E.B. (1) + LED 1 W	GX24q-3	LB3315-CLV	LB3215-CLV	LB3115-CLV	LB4315-CLV

(1) EEI = A2 / $\lambda \geq 0,95$

Standby light: LED 1 W, 350 mA, 87 lm, 4000 K, IRC > 80


BANG SQUARE + CORRIDOR FUNCTION







220-240 V AC / 50-60 Hz   RoHS

LAMP					OPAL
 1 x 18 W TC-DE E.B. DALI	G24q-2	LB3307-BHD	LB3207-BHD	LB3107-BHD	LB4307-BHD
 1 x 26 W TC-DE E.B. DALI	G24q-3	LB3309-BHD	LB3209-BHD	LB3109-BHD	LB4309-BHD
 1 x 32 W TC-TE E.B. DALI	GX24q-3	LB3315-BHD	LB3215-BHD	LB3115-BHD	LB4315-BHD

Requires external control (remote presence detector or other master luminaire, etc.) to activate the Corridor function.

BANG SQUARE + EXTINCTION WARNING FUNCTION

220-240 V AC / 50-60 Hz   RoHS



LAMP					OPAL
 1 x 18 W TC-DE E.B.	G24q-2	LB3307-OPE	LB3207-OPE	LB3107-OPE	LB4307-OPE
 1 x 26 W TC-DE E.B.	G24q-3	LB3309-OPE	LB3209-OPE	LB3109-OPE	LB4309-OPE
 1 x 32 W TC-TE E.B.	GX24q-3	LB3315-OPE	LB3215-OPE	LB3115-OPE	LB4315-OPE
















Requires external control (remote presence detector or other master luminaire, etc.) to activate the Extinction warning function.

 Anti-vandal tool see pages 208-209.

BANG SQUARE + DETECTION



BANG SQUARE + DETECTION








220-240 V AC / 50-60 Hz   RoHS

LAMP					OPAL
 Max. 60 W halo. 23 W CFLi + Easy-Sensor® Pro	E27	LB3321	LB3221	LB3121	LB4321
 Max. 60 W halo. 23 W CFLi + Compact Sensor	E27	LB3331	LB3231	LB3131	LB4331
 1 x 18 W CFLi Easy-Sensor® Pro + Osram Dulux Facility 4000 K	E27	LB3322	LB3222	LB3122	LB4322
 1 x 18 W CFLi Compact Sensor + Osram Dulux Facility 4000 K	E27	LB3332	LB3232	LB3132	LB4332
 1 x 18 W TC-DE E.B. + Easy-Sensor® Pro	G24q-2	LB3326	LB3226	LB3126	LB4326
 1 x 18 W TC-DE E.B. + Compact Sensor	G24q-2	LB3336	LB3236	LB3136	LB4336
 1 x 18 W TC-DE E.B. (1) + Easy-Sensor® Pro	G24q-2	LB3327	LB3227	LB3127	LB4327
 1 x 18 W TC-DE E.B. (1) + Compact Sensor	G24q-2	LB3337	LB3237	LB3137	LB4337
 1 x 26 W TC-DE E.B. (1) + Easy-Sensor® Pro	G24q-3	LB3329	LB3229	LB3129	LB4329
 1 x 26 W TC-DE E.B. (1) + Compact Sensor	G24q-3	LB3339	LB3239	LB3139	LB4339
 1 x 32 W TC-TE E.B. (1) + Easy-Sensor® Pro	GX24q-3	LB3325	LB3225	LB3125	LB4325
 1 x 32 W TC-TE E.B. (1) + Compact Sensor	GX24q-3	LB3335	LB3235	LB3135	LB4335

(1) EEI = A2 / λ ≥ 0.95



BANG SQUARE + DETECTION + STANDBY LIGHT










220-240 V AC / 50-60 Hz   RoHS

LAMP					OPAL
 Max. 60W halo. 23W CFLi Easy-Sensor® Pro + LED 1 W	E27	LB3321-CLV	LB3221-CLV	LB3121-CLV	LB4321-CLV
 Max. 60W halo. 23W CFLi Compact Sensor + LED 1 W	E27	LB3331-CLV	LB3231-CLV	LB3131-CLV	LB4331-CLV
 1 x 18 W CFLi Easy-Sensor® Pro + Osram Dulux Facility 2 500°K + LED 1 W	E27	LB3322-CLV	LB3222-CLV	LB3122-CLV	LB4322-CLV
 1 x 18 W CFLi Compact Sensor + Osram Dulux Facility 2 500°K + LED 1 W	E27	LB3332-CLV	LB3232-CLV	LB3132-CLV	LB4332-CLV


Standby light: LED 1 W, 350 mA, 87 lm, 4000 K, IRC > 80










BANG SQUARE + DETECTION + CORRIDOR FUNCTION


220-240 V AC / 50-60 Hz   RoHS

LAMP					OPAL
 1 x 18 W TC-DE E.B. + Easy-Sensor® Pro detection	G24q-2	LB3327-BHD	LB3227-BHD	LB3127-BHD	LB4327-BHD
 1 x 18 W TC-DE E.B. + Compact Sensor	G24q-2	LB3337-BHD	LB3237-BHD	LB3137-BHD	LB4337-BHD
 1 x 26 W TC-DE E.B. + Easy-Sensor® Pro detection	G24q-3	LB3329-BHD	LB3229-BHD	LB3129-BHD	LB4329-BHD
 1 x 26 W TC-DE E.B. + Compact Sensor	G24q-3	LB3339-BHD	LB3239-BHD	LB3139-BHD	LB4339-BHD
 1 x 32 W TC-TE E.B. + Easy-Sensor® Pro detection	GX24q-3	LB3325-BHD	LB3225-BHD	LB3125-BHD	LB4325-BHD
 1 x 32 W TC-TE E.B. + Compact Sensor	GX24q-3	LB3335-BHD	LB3235-BHD	LB3135-BHD	LB4335-BHD

BANG SQUARE + DETECTION + EXTINCTION WARNING FUNCTION

220-240 V AC / 50-60 Hz   RoHS

LAMP					OPAL
 1 x 18 W TC-DE E.B. + Easy-Sensor® Pro detection	G24q-2	LB3327-OPE	LB3227-OPE	LB3127-OPE	LB4327-OPE
 1 x 18 W TC-DE E.B. + Compact Sensor	G24q-2	LB3337-OPE	LB3237-OPE	LB3137-OPE	LB4337-OPE
 1 x 26 W TC-DE E.B. + Easy-Sensor® Pro detection	G24q-3	LB3329-OPE	LB3229-OPE	LB3129-OPE	LB4329-OPE
 1 x 26 W TC-DE E.B. + Compact Sensor	G24q-3	LB3339-OPE	LB3239-OPE	LB3139-OPE	LB4339-OPE
 1 x 32 W TC-TE E.B. + Easy-Sensor® Pro detection	GX24q-3	LB3325-OPE	LB3225-OPE	LB3125-OPE	LB4325-OPE
 1 x 32 W TC-TE E.B. + Compact Sensor	GX24q-3	LB3335-OPE	LB3235-OPE	LB3135-OPE	LB4335-OPE

 Anti-vandal tool see pages 208-209.